

5. AP Glass Door (Floor Spring Operated) – Service Checklist

Checklist for service and inspection of all-glass doors with floor spring control systems.

General Inspection

- ☐ Glass door leaf securely fixed into patch fittings
- ☐ Visual inspection of glass for chips, cracks or delamination
- ☐ Top and bottom patch fittings checked and tightened
- ☐ Ensure correct door alignment and margin within frame or surround

Floor Spring Mechanism

- ☐ Cover plate removed and floor spring body inspected
- ☐ Check for oil leaks from floor spring
- ☐ Door closing and latching speeds adjusted as required
- ☐ Check for smooth and silent operation during opening and closing
- ☐ Ensure floor spring spindle engagement is firm with bottom patch

Hardware & Accessories

- ☐ Top pivot or corner bracket inspected for wear or play
- ☐ Patch locks tested for secure operation and correct strike engagement
- ☐ Pull handles or D-handles securely fixed with no movement
- ☐ Check any additional locking mechanisms (floor bolts, euro cylinders)

Seals & Safety

- ☐ Check any glass edge protection seals (if fitted)
- ☐ Confirm edge gaps allow smooth swing with no glass contact
- ☐ Inspect threshold or floor clearance to prevent drag or snagging
- ☐ Confirm signage is present and compliant (manifestation visibility)

Functional Test

- ☐ Open/close tested 5x – door moves freely and self-centres
- ☐ Door latches securely into any strike plate (if applicable)
- ☐ No over-travel, bounce-back or sticking in any direction

- ☐ Confirm emergency access or manual override works if installed

Final Checks & Documentation

- ☐ Service log completed and signed
- ☐ Any worn components or adjustments noted
- ☐ End-user updated on door condition and next service date
- ☐ Confirm glass system is safe and functional in line with EN standards